

# CIS CLEAR 003

CLEAR RTV SILICONE ADHESIVE SEALANT

PRODUCT CATEGORY: SILICON SEALANT

## PRODUCT DESCRIPTION

CIS Clear 003 Silicone Adhesive Sealant is a general purpose, single component, room temperature vulcanizing (RTV) compound, designed for the sealing of mechanical assemblies. Upon curing from the exposure to moisture in the air, this non-sagging paste forms a tough, flexible, waterproof seal of silicone rubber, which resists aging, weathering and thermal cycling without hardening, shrinking or cracking.

## PRODUCT BENEFITS

- Easy application
- Applied to horizontal or vertical surfaces
- Waterproofs
- Insulates
- Unaffected by vibration
- Non-flammable
- Non-toxic

**TYPICAL APPLICATIONS CIS CLEAR 003 SILICONE ADHESIVE SEALANT IS AN EXCELLENT ALLPURPOSE ADHESIVE/SEALANT FOR THE FOLLOWING MATERIALS:**

- Metal
- Glass
- Wood
- Plastic
- Silicone resin
- Vulcanized silicone rubber.
- Ceramics
- Natural and synthetic fibers
- Painted surfaces Bonds, seals, repairs, mends and secures:
- Windshields (not for installation)
- Windows
- Door frames
- Vinyl tops



## INSTRUCTIONS FOR CIS CLEAR 003

1. Clean and dry all flange surfaces to be sealed.
2. Remove black cap from top of extension nozzle.

# CIS CLEAR 003

CLEAR RTV SILICONE ADHESIVE SEALANT

PRODUCT CATEGORY: SILICON SEALANT

3. Turn nozzle extension one complete turn (360°) counterclockwise.
  4. Depress finger trigger and apply a continuous 1/16 inch to 1/8 inch Power Bead to one surface.
  5. Apply a continuous and even bead of silicone to one surface.
  6. Assemble parts immediately while silicone is still wet.
- Secure or tighten as required, avoiding excessive squeeze-out.
7. Pressure should be applied to parts for 24 hours until the silicone is fully cured

## PACKAGING

250 ml Cartridge