

# CIS CRACK FIX

NON SHRINKING HIGH STRENGTH MODIFIED FILLER FOR CRACK REPAIR

PRODUCT CATEGORY: CRACK FILLER CEMENT

## PRODUCT DESCRIPTION

CIS CRACK FIX POWDER is a cement based powder material for filling cracks in plastered surfacetatic Cracks filled with CIS crack fix Powder enhances the subsequent paintings quality and life.

## AREAS OF APPLICATION

- To fill the static cracks of upto 5 mm sizes in horizontal or vertical areas of buildings & structures.
- To level the undulation of the unplastered or plastered ceilings and walls before painting.
- To provide smooth finish to brick, stone, and wood works.

## METHOD OF APPLICATION

### SURFACE PREPARATION

- Remove old caulk from joints. The edges of the joints should be neat and sound.
- Make sure that surface is clean & free from puddle of water.
- The surface should be free of loose debris.
- Contaminations of oil, grease or bitumin should be completely cleaned.
- Damp wood should be allowed to dry out and decayed wood should be removed.
- Roughen smooth surfaces to give a good key.

## APPLICATION

For crack filling – Fill the mixed paste into the crack by spatula or putty knife blade. Fill excess material and tool it by putty knife blade pressing against crack so that air voids get filled. By wet finger tool the surface of material in to a concave nature by pressing against joint edges.

- For Surface leveling – The mixed smooth paste should be applied by painter blade on the dampened wall or ceiling. The material should be applied at the desired thickness in bottom- to -up fashion to avoid blade marks. For multiple coat applications the previous coat should be allowed to cure for minimum 6 hrs. The subsequent coat should be at the right angle to the previous coat.



# CIS CRACK FIX

NON SHRINKING HIGH STRENGTH MODIFIED FILLER FOR CRACK REPAIR

PRODUCT CATEGORY: CRACK FILLER CEMENT

- For wood grain & pipe lagging – For wood grain, apply the buttery consistency mixed material by brush. Mix mineral wool with the buttery mix for pipe lagging & awkward places.

## COVERAGE

16- 20 running meters/kg for 5 mm x 5 mm groove

## SHELF LIFE & STORAGE

12 months from date of manufacturing. Store in a cool & dry place, away from sun light

## PACKING

5 KG, 25 KG